

Applicant: Markku Kyytsönen et al.  
PCT App. No.: PCT/FI2003/000961

### Remarks

Claims 13–30 remain pending in the application.

In claim 13 “a threaded path” is supported in FIG. 1, in paragraph [0008], and in paragraph [0023].

Claims 16, 23, 24, and 29 distinguish between paper grades with a Hunter Gloss % of less than 50 % and a PPS of greater than 2 micrometers, and paper grades with a Hunter Gloss % of greater than 50 % and a PPS of less than 2 micrometers, this limitation is supported by FIG. 2 and the distinction made in paragraph [0037] between NP, SC-C and MFC grades, and SC-A, SC-B, LWC and WFC grades.

Claim 20 is based on the description of OptiLoad® , Janus® and Prosoft® calenders found at Paragraphs [0029], [0032], and [0007].

Applicant believes that no new matter has been added by these amendments and that the application, as amended, is ready for examination. Favorable action thereon is respectfully solicited.

Respectfully submitted,



Patrick J. G. Stiennon, Reg. No. 34934  
Attorney for Applicant  
P.O. Box 1667  
Madison, Wisconsin 53701-1667  
(608) 250-4870  
Amdt1.app

JC18 Rec'd PCT/PTO 30 JUN 2005

In The United States Patent And Trademark Office

10/541165

Applicant: Markku Kyytsönen et al.

Date: June 30, 2005

Date Filed: Simultaneously herewith

Docket No.: FORSAL-105

PCT App. No.: PCT/FI2003/000961

For: Method for Calendering a Fibrous Web and a Calender

**Certificate of Express Mailing**

I hereby certify that this document is being deposited with  
the United States Postal Service "Express Mail Post Office to  
Addressee" service under 35 C.F.R. §1.10

on June 30, 2005

with Mailing Label No. EV 728 025 704 US

and is addressed to the Commissioner for Patents, P.O. Box  
1450, Alexandria, VA 22313-1450



Signature

Patrick J. G. Stiennon, Reg. No. 34934

Name of applicant, assignee or Registered Representative

**Marked Up Copy of Substitute Specification under 37 C.F.R. 1.125(b)(2)**

**TITLE OF THE INVENTION**

Method for ~~f~~cCalendering a ~~f~~fFibrous ~~web and a calender~~

~~f~~Web and a Calender

**CROSS REFERENCES TO RELATED APPLICATIONS**

**This application is a U.S. national stage application of International App. No. PCT/FI2003/000961, filed Dec. 16, 2003, the disclosure of which is incorporated by reference herein, and claims priority on Finnish App. No. 20030003, Filed Jan. 2, 2003.**

5

**STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER  
FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT**  
**Not applicable.**

## **BACKGROUND OF THE INVENTION**

**[0001]** The present invention relates to paper, pulp, board or other similar fibrous web machines. More specifically, the present invention relates to calenders of fibrous web machines and, in particular, the present invention relates to a method for calendering a fibrous web in a calender which includes at least two roll stacks which each have at least three rolls, and in which calender the fibrous web is passed to run between each roll pair of each roll stack. The invention also relates to a calender which includes at least two roll stacks which each have at least three rolls, and in which calender a fibrous web has been passed to run between each roll pair of each roll stack.

**[0002]** Calendering is a method by means of which attempts are generally made to improve the properties of a web-like material, such as a paper web, in particular, its thickness profile, smoothness, gloss, surface porosity and transperence. In the calendering process, a paper web is passed into a nip formed between rolls pressed against each other, in which nip the paper web is deformed due to the effect of temperature, moisture and nip pressure, whereby the physical properties of the paper web can be affected by regulating the above-mentioned parameters and the time of action. The good physical properties achieved by calendering result in improved print quality, thus giving a competitive advantage to the paper manufacturer.

**[0003]** Up to the mid 1990s, calenders comprised three main categories, which are typically single- or double-nip hard-nip calenders and soft calenders as well as multi-nip supercalenders. All these calender types have their advantages and disadvantages.

**[0004]** Shoe or so-called long-nip calendering has been found to be generally good for producing low-gloss paper grades, i.e. grades having a Hunter gloss % below 40. When a higher gloss is required, the nip pressure is, however, not sufficient to produce gloss. With continuously increasing running speeds, calendering is

becoming a bottleneck in the papermaking process and adequate quality is not achieved by means of today's hard-nip calenders. The drawbacks of today's papermaking process also include the fact that the loss of bulk increases when gloss is improved and that to achieve adequate quality it is necessary to employ abundantly coated webs and/or use off-line calendering, in particular soft calendering and/or multi-nip calendering, whose known application is supercalendering. The direction in the processing of the fibrous web and thus also in calendering is, however, towards on-line arrangements to an ever-increasing degree, also when the intention is to produce higher-quality printing paper grades, such as SC and glossy coated papers. FIG. 2 illustrates with a broken line currently available different paper grades, which include, among other things,

- NP (NewsPrint) newsprint paper grades,
- SC (SuperCalendered) paper grades,
- MFC (Machine Finished Coated) fine paper grades,
- LWC (Light Weight Coated) paper grades, and
- WFC (WoodFree Coated) fine paper grades,

and today's calenders, which include

- a hard-nip i.e. machine calender,
- a soft calender, and
- a supercalender

for producing different paper grades. It can also be seen from FIG. 2 that a multi-nip supercalender is remaining as the only alternative when the aim is to manufacture high-quality, i.e. high-gloss and smooth, WFC, LWC and SC paper grades.

**[0005]** The good characteristics of the calendering technique common today are beginning to reach their physical limits and the surface properties of the fibrous web cannot be much improved any more without a risk of the surface being scratched. When running speeds simultaneously increase to be as high as 1600 m/min or more, a drawback is the shortening time of action of calendering, which leads to considerable capacity problems when producing high-quality paper grades, so that even three supercalenders are not necessarily sufficient to produce high quality at

high speeds, but even a fourth supercalender is needed, which is expensive both as an investment and in respect of operation.

**[0006]** Because of the development of the soft calender technology, polymer-coated rolls can be used in the calender today. A problem associated with this is, however, that if more than three rolls in the supercalender are provided with an elastic polymer coating, the quality of the fibrous web begins to deteriorate. To meet increasing quality requirements, three new calender types have been developed, which are the OptiLoad® calender developed by ~~the applicant~~ **Metso Paper, Inc.**, provided with a single roll stack and typically including 6-12 rolls and having as a special feature the possibility of affecting the linear loads of individual nips and providing the roll stack with a nip load even inversely increasing with respect to the force of gravity; the Janus® calender developed by Voith-Sulzer, provided with two roll stacks and typically including 6-10 rolls; and the Prosoft® calender developed by Küsters-Beloit, provided two roll stacks and typically including 6-14 rolls.

**[0007]** These new type of multi-nip calenders, which can be used both as on-line and off-line calenders, are standard types in today's calendering technique and they are based on enhanced utilization of an elastic roll coating, but they differ substantially from one another in respect of attainable calendering results.

## **SUMMARY OF THE INVENTION**

5 **[0008]** One object of the present invention is to reduce the weaknesses, drawbacks and problems associated with the known calendering technique and provide a novel calender which makes it possible to produce a fibrous web within a broader range of gloss and smoothness without a need for threading of the fibrous web and/or for shutdown of the fibrous web machine, i.e. to make it possible to change the grade of the fibrous web produced in on-line operation.

10 **[0009]** This object is achieved by means of the method and the calender of the invention mentioned at the beginning, which method is generally characterized in that in order to produce a selectable fibrous web grade, at least one roll pair in at least one roll stack is arranged to be in nip contact to form a nip that calenders a fibrous web.

15 **[0010]** In accordance with an advantageous embodiment of the method in accordance with the invention, at least one roll pair in each roll stack is arranged to be in nip contact to form in each roll stack at least one nip that calenders a fibrous web.

20 **[0011]** By means of the method in accordance with the invention, by increasing the number of closed i.e. calendering nips in the calender it is possible to produce higher-quality paper grades, such as SC-A, SC-B, LWC and WFC grades, and by decreasing the number of closed i.e. calendering nips in the calender it is possible to produce lower-quality paper grades, such as NP, SC-C and/or MFC grades.

25 **[0012]** The aim of the invention is also achieved by means of the calender mentioned at the beginning, which calender is generally characterized in that in order to produce a selectable fibrous web grade, at least one roll pair in at least one roll stack has been arranged to be in nip contact to form at least one nip that calenders a fibrous web.



**[0013]** An advantageous embodiment of the calender in accordance with the invention is characterized in that in order to produce a selectable fibrous web grade, at least one roll pair is in nip contact in each roll stack, whereby at least one nip that calenders a fibrous web is formed in each roll stack.

5 **[0014]** The invention can be employed to produce fibrous webs of different grades and to change the grade of the fibrous web during running in any combination of rolls. Advantageous calenders for applying the invention are, among other things, various multi-roll-stack calenders, such as, for example, OptiLoad®, Janus® and Prosoft® calenders. In that connection, it is to be recommended that the roll  
10 combination in two successive roll stacks of the calender is, for example, 2x3, 2x5, 2x7, 3+5, 5+5, 5+7.

**[0015]** As all rolls in the calender in accordance with the invention are movable with respect to each other, a fibrous web can be calendered on the calender while all nips are operating, in which connection all roll gaps in each roll stack of the calender  
15 are closed and form a closed nip, or while one/some of the nips is/are operating, in which connection at least one roll gap in at least one roll stack is open, i.e. a nip that does not calender the fibrous web. In that connection, different paper grades, such as NP, SC, MFC, LWC and WFC grades can be produced by regulating the number and/or nip load of closed i.e. calendering nips. Particularly advantageously,  
20 operation with one/some of the nips is suitable for the production of lower-quality paper grades, such as NP, SC-C and MFC grades, and operation with all nips is suitable for the production of high-quality paper grades, such as SC-A, SC-B, LWC and WFC grades.

**[0016]** In accordance with the invention, for moving rolls at least one roll stack of the calender includes power means arranged between carrier arms, support arms or bearing housings of roll pairs formed by rolls placed one upon the other in order to adjust nip load and/or to form an open nip and/or to form a closed nip between a roll pair by moving the rolls of the roll pair in a direction substantially away from each other or towards each other.

**[0017]** With respect to the advantages of the invention it may be mentioned that calendering capacity can be improved by the possibility of creating an on-line process line using a single calender arrangement for producing different grades, as an example of this can be mentioned a process line that makes it possible to produce fibrous webs of different grades, such as a paper web whose grade can be selected between the grades newsprint ... SC-A. An advantage is also that the fibrous web production line need not be stopped for the duration of maintenance of the calender. In that case, in on-line operation it is possible to replace, for example, a soft roll with a thermo roll or vice versa, thus achieving a different calender in respect of its production characteristics.

**[0018]** In the following, the invention will be described by way of example by means of one advantageous embodiment of the invention, which is accomplished in ~~{the applicant's}~~ **Metso Paper, Inc.'s** OptiLoad® calender, with reference to the appended ~~{drawing in which}~~ **drawings**.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0019]** FIG. 1 schematically illustrates a calender comprising two roll stacks, such as, for example, an OptiLoad®, Janus® or Prosoft® supercalender having two roll stacks, to make use of the present invention~~;~~.

5 **[0020]** FIG. 2 illustrates paper grades attainable by means of ordinary known calendering techniques and paper grades attainable by the method and the calender in accordance with the invention in a system of Hunter ~~{gloss/~~  
~~smoothness}~~gloss/smoothness coordinates~~;~~.

10 **[0021]** FIG. 3 shows one embodiment for moving the rolls of one roll pair in the calender with respect to each other~~;~~.

**[0022]** FIG. 4 shows a second embodiment for moving the rolls of one roll pair in the calender with respect to each other~~;~~.

**[0023]** FIG. 5 shows a third embodiment for moving the rolls of one roll pair in the calender with respect to each other~~;~~ ~~and~~.

15 **[0024]** FIG. 6 shows a fourth embodiment for moving the rolls of one roll pair in the calender with respect to each other.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

**[0025]** **F~~fig~~I****G.** 1 is a schematic view of a supercalender 10 provided with two roll stacks. Hereafter the supercalender provided with two roll stacks is referred to by the definition calender 10 for the sake of simplicity. The calender 10 shown in **F~~fig~~I****G.**

1 includes two roll stacks 11L, 11R. In both roll bodies of the calender, a top roll 1, a bottom roll 5 and a **fcentre****center** roll 3 are soft rolls having an elastic shell and a thermo roll 2, 4 having a hard-surface shell is arranged between the top roll 1 and the **fcentre****center** roll 3 as well as between the bottom roll 5 and the **fcentre****center** roll 3.

**[0026]** In the calender 10 of **F~~fig~~I****G.** 1, a fibrous web W runs in both roll stacks 11L, 11R, between which the travel of the web is guided by a guide roll 16, meandering between each roll pair 1, 2; 2, 3; 3, 4; 4, 5 around spreader rolls 15 of the web. In both roll stacks 11L, 11R there are four roll gaps NC, NO, one between each roll pair 1, 2; 2, 3; 3, 4; 4, 5. In the embodiment of **F~~fig~~I****G.** 1, a roll pair is formed of an elastic roll and a thermo roll. When the rolls of a roll pair are in shell contact with each other, a nip NC that calenders the web is formed between the rolls, and when the rolls of a roll pair are out of shell contact with each other, a roll gap NO that does not calender the web W is formed.

**[0027]** In accordance with the basic idea of the invention, to produce a selectable fibrous web grade, at least one roll pair in at least one roll stack is arranged to be in nip contact to form a nip that calenders the fibrous web. In other words, in order to produce a selectable fibrous web grade, in the calender in accordance with the invention there is in at least one roll stack 11 at least one roll pair 1, 2 in nip i.e. shell contact, whereby at least one nip NC that calenders the fibrous web is formed.

**[0028]** To form two nips NC that calender the web W, in the embodiment of **F~~fig~~I****G.** 1, the top roll 1 and the upper thermo roll 2 as well as the bottom roll 5 and the lower thermo roll 4 are arranged to be in nip contact in the left-hand roll stack 11L of the calender 10 by moving the rolls in the vertical direction, i.e. more

generally in the direction of the roll stack. To form three nips NC that calender the web W, in the embodiment of ~~Ffig~~FIG. 1, the top roll 1 and the upper thermo roll 2, the upper thermo roll 2 and the ~~centre~~center roll 3, as well as the bottom roll 5 and the lower thermo roll 4 are arranged to be in nip contact in the right-hand roll stack 11R by moving the rolls. In the calender 10 of the embodiment of ~~Ffig~~FIG. 1, the rolls 1-4 in both roll stacks 11L, 11R are movable by means of loading or carrier arms 6. In addition, by means of the carrier arms 6 it is possible to adjust the magnitude of the compression or loading force applied on the fibrous web by the nip NC between the rolls which are in shell or nip contact. In the embodiment of ~~Ffig~~FIG. 1, in both roll stacks 11L, 11R of the calender 10, the bottom roll 5 is loaded by a hydraulic cylinder 7 which is located underneath the bottom roll 5 and which advantageously acts in the same manner as the loading or carrier arms 6 on the non-rotating shaft of the roll or on the bearing housings of the roll shell journalled to be rotatable on the shaft.

[0029] Reference is made to ~~Ffig~~FIG. 3 showing one embodiment for moving the rolls of one roll pair of the calender with respect to each other, for example, in the direction of the roll stack. In the embodiment of ~~Ffig~~FIG. 3, which is particularly suitable for ~~the applicant's~~Metso Paper, Inc.'s OptiLoad® calender, a power member 81, which is advantageously a hydraulic or pneumatic cylinder or a power screw, is disposed between the loading, support or relief arms 6 of the rolls, which arms turn in a lever-like manner at one end thereof. When the length of the power member 81 is increased, the loading, support or relief arms 6 turn in a lever-like manner away from each other, whereby the nip load between the rolls of the roll pair 2, 3 is relieved or the rolls come out of shell contact and form an open nip NO of ~~Ffig~~FIG. 3 that does not calender the fibrous web W. When the length of the power means 81 is shortened, the loading, support or relief arms 6 turn in a lever-like manner towards each other, whereby the nip load between the rolls of the roll pair 2, 3 increases and the nip NC that calenders the fibrous web W is closed.

[0030] Reference is made to ~~Ffig~~FIG. 4 showing a second embodiment for moving

the rolls of one roll pair of the calender with respect to each other, for example, in the direction of the roll stack. In the embodiment of F~~fig~~I~~G~~. 4, which embodiment like the embodiment of F~~fig~~I~~G~~. 3 is suitable in particular for ~~the~~  
~~applicant's~~Metso Paper Inc.'s OptiLoad® calender, a power means 81, which is  
5 advantageously a hydraulic or pneumatic cylinder or a power screw, is disposed between the loading, support or relief arms 6 of the rolls, which arms turn in a lever-like manner at one end thereof. The embodiment of F~~fig~~I~~G~~. 4 differs from the embodiment of F~~fig~~I~~G~~. 3 in that the loading, support or relief arms 6 are connected by means of an articulated joint 9 to form two parts. In this embodiment of F~~fig~~I~~G~~.  
10 4, the power means is arranged on a second part of the loading, support or relief arms 6 on the side of the roll 2, so that a first part of the loading, support or relief arms 6 can be kept unmovable and non-turning about its fulcrum point in a lever-like manner, which substantially facilitates the locking of the loading, support or relief arms 6 in a desired orientation. When the length of the power means 81 is increased,  
15 the second parts of the loading, support or relief arms 6 on the side of the rolls 2, 3 turn in a lever-like manner away from each other, whereby the nip load between the rolls of the roll pair 2, 3 is relieved or the rolls come out of shell contact and form an open nip NO of F~~fig~~I~~G~~. 4 that does not calender the fibrous web W. When the length of the power means 81 is shortened, the second parts of the loading, support  
20 or relief arms 6 on the side of the rolls 2, 3 turn in a lever-like manner towards each other, whereby the nip load between the rolls of the roll pair 2, 3 increases and the nip NC that calenders the fibrous web W is closed.

[0031] Reference is made to F~~fig~~I~~G~~. 5 showing one embodiment for moving the rolls of one roll pair of the calender with respect to each other. The embodiment of  
25 F~~fig~~I~~G~~. 5 substantially corresponds in operation to the embodiment of F~~fig~~I~~G~~. 3 and is thus suitable for use in particular in ~~the applicant's~~Metso Paper, Inc.'s OptiLoad® calenders. In this embodiment of F~~fig~~I~~G~~. 5, a power means 82 includes a wedge means that is movable by means of a hydraulic, pneumatic or a similar actuator to and fro, advantageously in a direction transverse to the ~~centre~~center  
30 line passing through the ~~centre~~center axes of the rolls of the roll pair 2, 3. In the

embodiment of **FfigIG. 5**, the wedge means of the power means 82 acts between the loading, support or relief arms 6 of the rolls such that when the wedge means is moved by means of the power means away from the roll pair 2, 3, the nip load between the rolls is relieved or the rolls come out of shell contact and form an open nip NO of **FfigIG. 5** that does not calender the fibrous web W, and such that when the wedge means is moved towards the roll pair 2, 3, the nip load between the rolls increases and the nip NC that calenders the fibrous web W is closed.

**[0032]** In connection with the embodiment of **FfigIG. 5** it must be noted that the wedge means can also be arranged to act between non-rotating shafts of the roll pair 2, 3 or between bearing housings of the rolls journalled to be rotatable, so that the embodiment is suitable for use in calenders in which the rolls 1-5 are not provided with loading, support or relief arms 6, such as in Janus® and Prosoft® calenders.

**[0033]** Reference is made to **FfigIG. 6** showing one embodiment for moving the rolls of one roll pair of the calender with respect to each other. In the embodiment of **FfigIG. 6**, which embodiment is suitable for use in calenders whose rolls 1-5 are not provided with loading, support or relief arms 6, a power means 83 is arranged between the non-rotating shafts of the roll pair 2, 3 or between the bearing housings of the rolls journalled to be rotatable, which power means 83 is advantageously a hydraulic or pneumatic cylinder or a power screw. When the length of this kind of power means 83 is increased, the nip load between the rolls of the roll pair 2, 3 is relieved or the rolls come out of shell contact and form an open nip NO of **FfigIG. 6** that does not calender the fibrous web W. When the length of this kind of power means 83 is shortened, the nip load between the rolls of the roll pair 2, 3 increases and the nip NC that calenders the fibrous web W is closed.

**[0034]** In connection with the invention it must be emphasized that the number of the rolls in the roll stack 11L, 11R is not essential to the present invention. In accordance with the invention it is advantageous, however, that the roll combination

of two successive roll stacks is selected from the group which includes 2x3, 2x5, 2x7, 3+5, 5+5 and 5+7 rolls. When the number of rolls is other than the five rolls shown in ~~F~~**fig**IG. 1, i.e. n rolls, in the roll stack there are correspondingly more or fewer roll gaps than the four roll gaps of ~~F~~**fig**IG. 1, i.e. n-1 roll gaps. Said roll combination is provided, for example, by two successive roll stacks of ~~the~~  
5 **applicant's** Metso Paper, Inc.'s OptiLoad® supercalender, by two successive roll stacks of Voith-Sulzer's Janus® supercalender or by two successive roll stacks of Küsters-Beloit's Prosoft® supercalender.

[0035] When the purpose of the calender in accordance with the invention is to  
10 produce smoother and glossier paper qualities of different paper grades, such as WFC, LWC and SC paper grades, at least one roll pair 1, 2; 2, 3; 3, 4; 4, 5 is arranged to be in nip contact in each roll stack 11L, 11R and thus to form at least one nip NC calendering the fibrous web W in each roll stack.

[0036] By means of the calender in accordance with the invention it is thus  
15 possible to calender a fibrous web while all nips are operating or while one/some of the nips is/are operating. When all nips are operating, all roll gaps in each roll stack 11L, 11R of the calender 10 are closed forming closed nips NC that calender the fibrous web W. A roll gap is closed to form a web-calendering nip NC by moving the rolls of a roll pair 1, 2; 2, 3; 3, 4; 4, 5 defining the roll gap into shell i.e. nip  
20 contact with each other, for example, in the direction of the roll stack. Operation with one/some of the nips operating differs from operation with all nips operating in that at least one roll gap in at least one roll stack 11L, 11R of the calender 10 is an open roll gap or nip NO, in which the fibrous web is not calendered.

[0037] Reference is made to ~~F~~**fig**IG. 2, which shows with a broken line the paper grade ranges which can be produced on known calenders and with an unbroken line  
25 the range which can be produced on the calender 10 in accordance with the present invention. It is characteristic of the prior-art calendering technique that, as the starting point, a different calender type is intended for different paper grades. In



accordance with the present invention, many different paper grades, including NP, SC, MFC, LWC and MFC grades, can be produced by means of one and the same calender of the invention, the type of said calender being a supercalender provided with at least two roll stacks, by regulating the number of the calendaring nips NC, i.e. operation with all or one/some of the nips, and the nip load of the calendaring nips NC. In that connection, operation with one/some of the nips is most suitable for the production of lower-quality paper grades, such as NP, SC-C and MFC grades, and operation with all nips is favorably suitable for the production of high-quality paper grades, such as SC-A, SC-B, LWC and WFC grades.

**[0038]** In summary of the invention it may thus be stated that, at the same time as the present invention allows complete on-line or off-line operation, it is possible merely  
— by increasing the number of calendaring nips NC in the calender 10 to produce higher-quality paper grades, and  
- by decreasing the number of calendaring nips NC in the calender 10 to produce lower-quality paper grades.

**[0039]** Above, the invention has been described only by way of example by means of one of its advantageous embodiments. By this it is, however, not desired to limit the invention to such a single exemplifying embodiment and, as is clear to a person skilled in the art, many alternative arrangements and variations are feasible within the scope of protection of the new and inventive basic idea defined in the appended claims.

**[0040]** Thus, it must be emphasized that the number of the roll stacks 11L, 11R of the calender 10 may differ from the two roll stacks shown in **Fig. 1** and that the roll stack can in itself be formed of a roll order other than the roll order shown in **Fig. 1**, in which there are alternately soft rolls and thermo rolls, so that to form a roll pair, the roll stack 11L, 11R may comprise, for example two opposing thermo rolls, in which connection the roll pair can form a hard nip and the roll stack can

serve as a hard-nip i.e. machine calender, or two opposing soft rolls, in which connection the roll pair forms therebetween a reversing nip that does not calender the web W to calender the web on two sides in one roll stack 11L, 11R.

~~{Abstract~~

~~The invention relates to a method and a calender for calendaring a fibrous web, which}~~                      **ABSTRACT OF THE DISCLOSURE**

~~A~~ calender includes at least two roll stacks which each have at least three rolls, and  
5 in each of which the web path of ~~{the}~~a fibrous web meanders between each roll pair  
of the ~~{roll}~~ stack. ~~{The method is characterized in that it}~~In order to produce a  
selectable fibrous web grade, the ~~{fibrous}~~ web is passed between each roll pair of  
each ~~{roll}~~ stack~~{of the calender}~~, so that at least one roll pair in at least one ~~{roll}~~  
stack is~~{arranged to be}~~ in nip contact to form a nip that calenders the ~~{fibrous}~~  
10 web. The~~{calender is characterized in that the fibrous}~~ web runs between each  
roll pair of each roll stack and~~{that}~~, in order to produce a selectable fibrous web  
grade, a selectable number of rolls ~~{has been arranged to be}~~is in nip contact with  
each other in each~~{roll}~~ stack to form at least one nip that calenders the fibrous web.